

Report No.:

Test Time: 2025-09-20 16:49

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: 38D

Luminous Width (mm): -20

Current: 0.088 A

Power Factor: 0.505

Luminous Length (mm): -215

Voltage: 230.7 V

Power: 10.30 W

Photometric Results

CIE Class: Direct

Measurement Flux: 1018.2 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H40.1

Vertical Diffuse Angle(50%): V40.1

Luminaire Efficacy Rating (LER): 98.90

Max. Intensity: 2036.19 cd

S/MH(C0/C180): 0.66

Total Rated Lamp Lumens: 1018.2 lm

Efficiency: 100%

Upward Ratio: 0%

Central Intensity: 2001.78 cd


Pos of Max. Intensity: H0 V4

S/MH(C90/C270): 0.66

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0



Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 2036 cd

(10%): 204 cd	(16%): 326 cd
(25%): 509 cd	(40%): 814 cd
(63%): 1283 cd	(100%): 2036 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 20.2 lx

(1%): 0.2 lx	(2%): 0.4 lx
(5%): 1.0 lx	(10%): 2.0 lx
(20%): 4.0 lx	(50%): 10.1 lx
(100%): 20.2 lx	


C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 2001.8 lx


(1%): 20.0 lx	(2%): 40.0 lx
(5%): 100.1 lx	(10%): 200.2 lx
(20%): 400.4 lx	(50%): 1000.9 lx
(100%): 2001.8 lx	

C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

The Average Illuminance Effective Figure



UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	16.3	17.0	16.6	17.2	17.4	15.8	16.5	16.0	16.7	16.9
3H	16.2	16.8	16.5	17.1	17.3	15.6	16.3	15.9	16.5	16.8
4H	16.1	16.7	16.4	17.0	17.3	15.6	16.2	15.9	16.5	16.7
6H	16.1	16.6	16.4	16.9	17.2	15.5	16.1	15.8	16.4	16.7
8H	16.0	16.6	16.4	16.9	17.2	15.5	16.1	15.9	16.4	16.7
12H	16.1	16.6	16.4	16.9	17.2	15.6	16.1	15.9	16.4	16.7
X=4H Y=2H	16.1	16.7	16.4	17.0	17.2	15.5	16.2	15.9	16.4	16.7
3H	16.0	16.5	16.3	16.8	17.1	15.4	16.0	15.8	16.3	16.6
4H	15.9	16.4	16.3	16.7	17.1	15.3	15.8	15.7	16.2	16.5
6H	15.8	16.3	16.3	16.6	17.0	15.3	15.7	15.7	16.1	16.5
8H	15.9	16.3	16.3	16.6	17.0	15.3	15.7	15.8	16.1	16.5
12H	15.9	16.3	16.4	16.7	17.1	15.4	15.8	15.9	16.2	16.6
X=8H Y=4H	15.8	16.2	16.2	16.5	17.0	15.2	15.6	15.7	16.0	16.4
6H	15.7	16.1	16.2	16.5	16.9	15.2	15.5	15.7	16.0	16.4
8H	15.8	16.1	16.3	16.5	17.0	15.3	15.6	15.8	16.0	16.5
12H	16.0	16.2	16.4	16.7	17.2	15.5	15.7	16.0	16.2	16.7
X=12H Y=4H	15.7	16.1	16.2	16.5	16.9	15.2	15.5	15.6	16.0	16.4
6H	15.7	16.0	16.2	16.4	16.9	15.2	15.5	15.7	15.9	16.4
8H	15.8	16.0	16.3	16.5	17.0	15.3	15.6	15.8	16.0	16.5
Variations with the observer position at spacings:										
S=1.0H	+5.6/-11.1					+5.5/-10.5				
S=1.5H	+8.4/-12.0					+8.2/-11.4				
S=2.0H	+10.4/-12.4					+10.2/-11.7				

Calculate in accordance with CIE Pub.117. The table is revised with 1018lm ($8\log(F/F_0) = 0.1$).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	533	52.3
	FL (0°-30°)	456	44.8
	FM (30°-60°)	75	7.3
	FH (60°-80°)	1	0.1
	FVH (80°-90°)	1	0.1
	BACK LIGHT	485	47.7
	BL (0°-30°)	418	41.0
	BM (30°-60°)	66	6.4
	BH (60°-80°)	1	0.1
	BVH (80°-90°)	1	0.1
	UP LIGHT	0	0.0
	UL (90°-100°)	0	0.0
	UH (100°-180°)	0	0.0
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	2001.1	1.9	1.9	0.19	0.19
1.0-2.0	1998.2	5.7	7.7	0.56	0.75
2.0-3.0	1991.9	9.5	17.2	0.94	1.69
3.0-4.0	1982.0	13.3	30.4	1.30	2.99
4.0-5.0	1967.8	16.9	47.4	1.66	4.65
5.0-6.0	1948.3	20.5	67.9	2.01	6.66
6.0-7.0	1923.3	23.9	91.7	2.34	9.01
7.0-8.0	1892.0	27.1	118.8	2.66	11.67
8.0-9.0	1853.6	30.0	148.9	2.95	14.62
9.0-10.0	1808.0	32.7	181.6	3.21	17.83
10.0-11.0	1755.0	35.1	216.7	3.44	21.28
11.0-12.0	1694.6	37.0	253.7	3.64	24.92
12.0-13.0	1627.7	38.6	292.3	3.79	28.71
13.0-14.0	1555.0	39.8	332.1	3.91	32.62
14.0-15.0	1477.8	40.6	372.7	3.99	36.61
15.0-16.0	1397.1	40.9	413.7	4.02	40.63
16.0-17.0	1313.7	40.9	454.6	4.02	44.65
17.0-18.0	1229.3	40.5	495.1	3.98	48.63
18.0-19.0	1145.1	39.8	535.0	3.91	52.54
19.0-20.0	1061.7	38.9	573.8	3.82	56.36
20.0-21.0	980.4	37.6	611.5	3.70	60.06
21.0-22.0	901.7	36.2	647.7	3.56	63.61
22.0-23.0	825.8	34.7	682.4	3.40	67.02
23.0-24.0	753.7	33.0	715.3	3.24	70.26
24.0-25.0	685.6	31.2	746.5	3.06	73.32
25.0-26.0	621.1	29.3	775.8	2.88	76.20
26.0-27.0	560.5	27.4	803.2	2.69	78.89
27.0-28.0	503.4	25.5	828.7	2.50	81.39
28.0-29.0	449.3	23.5	852.2	2.31	83.70
29.0-30.0	397.9	21.5	873.7	2.11	85.81
30.0-31.0	348.6	19.4	893.1	1.91	87.72
31.0-32.0	301.8	17.3	910.4	1.70	89.42
32.0-33.0	258.5	15.2	925.6	1.50	90.91
33.0-34.0	219.3	13.3	938.9	1.30	92.22
34.0-35.0	184.5	11.5	950.4	1.13	93.34
35.0-36.0	154.1	9.8	960.2	0.96	94.31

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	128.3	8.4	968.6	0.82	95.13
37.0-38.0	106.8	7.1	975.7	0.70	95.83
38.0-39.0	89.1	6.1	981.8	0.60	96.43
39.0-40.0	74.6	5.2	987.0	0.51	96.94
40.0-41.0	62.8	4.5	991.5	0.44	97.38
41.0-42.0	53.1	3.9	995.3	0.38	97.76
42.0-43.0	45.0	3.3	998.6	0.33	98.08
43.0-44.0	38.2	2.9	1001.5	0.28	98.37
44.0-45.0	32.4	2.5	1004.0	0.24	98.61
45.0-46.0	27.3	2.1	1006.2	0.21	98.82
46.0-47.0	22.9	1.8	1008.0	0.18	99.00
47.0-48.0	18.9	1.5	1009.5	0.15	99.15
48.0-49.0	15.3	1.3	1010.8	0.12	99.27
49.0-50.0	11.8	1.0	1011.8	0.10	99.37
50.0-51.0	8.7	0.7	1012.5	0.07	99.44
51.0-52.0	6.0	0.5	1013.0	0.05	99.49
52.0-53.0	3.9	0.3	1013.3	0.03	99.53
53.0-54.0	2.4	0.2	1013.6	0.02	99.55
54.0-55.0	1.5	0.1	1013.7	0.01	99.56
55.0-56.0	1.2	0.1	1013.8	0.01	99.57
56.0-57.0	1.0	0.1	1013.9	0.01	99.58
57.0-58.0	0.9	0.1	1014.0	0.01	99.59
58.0-59.0	0.9	0.1	1014.1	0.01	99.60
59.0-60.0	0.9	0.1	1014.1	0.01	99.60
60.0-61.0	1.0	0.1	1014.2	0.01	99.61
61.0-62.0	1.0	0.1	1014.3	0.01	99.62
62.0-63.0	1.0	0.1	1014.4	0.01	99.63
63.0-64.0	1.1	0.1	1014.5	0.01	99.64
64.0-65.0	1.2	0.1	1014.7	0.01	99.66
65.0-66.0	1.3	0.1	1014.8	0.01	99.67
66.0-67.0	1.3	0.1	1014.9	0.01	99.68
67.0-68.0	1.2	0.1	1015.0	0.01	99.69
68.0-69.0	1.1	0.1	1015.1	0.01	99.70
69.0-70.0	1.0	0.1	1015.3	0.01	99.71
70.0-71.0	1.0	0.1	1015.4	0.01	99.72
71.0-72.0	1.1	0.1	1015.5	0.01	99.74

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	2001.8	2001.8								
G1.0	2014.9	1985.8								
G2.0	2025.8	1966.1								
G3.0	2033.1	1942.3								
G4.0	2036.2	1916.3								
G5.0	2032.7	1885.8								
G6.0	2024.0	1850.6								
G7.0	2007.4	1811.2								
G8.0	1983.0	1766.3								
G9.0	1948.9	1716.1								
G10.0	1906.7	1660.3								
G11.0	1854.0	1599.0								
G12.0	1793.3	1532.3								
G13.0	1725.2	1459.9								
G14.0	1650.1	1384.8								
G15.0	1568.8	1307.6								
G16.0	1483.5	1228.4								
G17.0	1393.9	1148.8								
G18.0	1304.1	1070.3								
G19.0	1214.7	991.2								
G20.0	1125.5	915.3								
G21.0	1038.8	841.9								
G22.0	954.3	771.7								
G23.0	872.2	704.8								
G24.0	795.6	642.0								
G25.0	723.2	581.5								
G26.0	654.8	525.0								
G27.0	590.0	472.1								
G28.0	529.7	421.6								
G29.0	473.0	373.0								
G30.0	419.5	326.3								
G31.0	367.5	281.1								
G32.0	317.9	240.7								
G33.0	271.4	203.9								
G34.0	230.3	171.6								
G35.0	192.4	143.6								
G36.0	160.0	120.3								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	132.4	100.7								
G38.0	109.4	84.9								
G39.0	90.6	71.6								
G40.0	75.4	60.8								
G41.0	62.9	52.0								
G42.0	52.9	44.5								
G43.0	44.8	37.8								
G44.0	38.0	32.2								
G45.0	32.2	27.3								
G46.0	27.0	22.9								
G47.0	22.7	18.9								
G48.0	18.9	15.4								
G49.0	15.1	11.9								
G50.0	11.9	8.4								
G51.0	8.9	5.6								
G52.0	6.4	3.2								
G53.0	4.2	1.8								
G54.0	2.5	1.1								
G55.0	1.5	1.0								
G56.0	1.1	1.0								
G57.0	1.1	0.7								
G58.0	1.1	0.7								
G59.0	1.0	0.7								
G60.0	0.8	1.0								
G61.0	1.1	1.0								
G62.0	1.1	1.0								
G63.0	1.1	1.0								
G64.0	1.1	1.1								
G65.0	1.1	1.4								
G66.0	1.3	1.4								
G67.0	1.3	1.1								
G68.0	1.3	1.1								
G69.0	1.0	1.0								
G70.0	0.8	1.1								
G71.0	1.1	1.1								
G72.0	1.1	1.1								
G73.0	1.1	1.1								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

